


PAC150S-S

PACKAGED AIR-COOLED 15 HP SINGLE CIRCUIT SEMI-HERMETIC



PRODUCT PERFORMANCE INFORMATION												
REFRIGERANT	COMPRESSOR OPER.	LFT	80°F AMB		90°F AMB		95°F AMB		100°F AMB		105°F AMB	
REFRIGERANT	TEMP. SUCTION RANGE	۴F	TONS	EER	TONS	EER	TONS	EER	TONS	EER	TONS	EER
R407C	10°F to 55°F	20	8.3	10.7	7.7	11.3	7.4	11.6	7.1	11.8	6.7	12.0
		35	11.4	12.4	10.6	13.3	10.2	13.7	9.9	14.1	9.5	14.4
		45	13.6	13.4	12.7	14.4	12.2	14.9	11.8	15.4	11.4	15.9
		55	15.8	14.2	14.8	15.4	14.3	16.0	13.7	16.5	13.2	17.2
		65	18.1	14.8	16.9	16.1	16.2	16.8	15.6	17.5	14.9	18.2
R404A	-10°F to 45°F	0	6.0	6.1	5.5	5.4	5.2	5.1	4.9	4.7	4.6	4.4
		10	7.6	7.1	6.9	6.2	6.6	5.8	6.3	5.4	6.0	5.1
		25	10.5	8.5	9.6	7.4	9.2	7.0	8.7	6.5	8.3	6.0
		40	13.7	9.8	12.5	8.5	11.9	7.9	11.4	7.4	10.8	6.9
		55	17.3	11.0	15.8	9.5	15.1	8.9	14.4	8.3	13.7	7.7

DRAKE REFRIGERATION INC

2900 SAMUEL DRIVE BENSALEM, PA 19020 (888) 289-7299 www.drakechillers.com



PAC150S-S

PACKAGED AIR-COOLED 15 HP SINGLE CIRCUIT SEMI-HERMETIC

FEATURE	BENEFIT					
Listings	ETL 3046941, UL STD 1995, CAN/CSA STD, C22.2 No. 236					
Micro Control Systems Controller	Open source, microprocessor built to operate in the HVAC/R industry					
Controls	BMS, BAS communications, remote access, monitoring services					
Stainless Steel Brazed Plate Evaporator	Corrosion resistant, fully insulated and selected upon requirements					
Copeland Semi-Hermetic Compressor	Industry leader, rebuildable, long lasting compressor Allows for soft-start and stepped capacity control from 50-100%					
Variable Capacity Control						
Compressor Crankcase Heater	Prevents compressor damage caused by cold refrigerant on startup					
Suction Accumulator	Protects the compressor from damage caused by liquid flood back by preventing liqu					
Suction Accumulator	from entering the compressor					
Water Flow Switch	Protects against process fluid freezing caused by pump failure					
Copper Tube/Aluminum Fin Condenser	Rust resistant and high CFM					
Compressor Vibration Eliminators	Eliminates vibration transfer and reduces noise					
Painted Galvanized Steel Metal Cabinet	Sturdy, corrosion resistance, professional appearance					
Insulated Process Fluid Lines	Maximum thermal efficiency					
Fosters: Tested	Ensures the unit meets the customer's performance designed criteria and arrives i					
Factory Tested	working order					
Full Refrigerant Charge	Hassle free and more efficient installation					
NEMA 3R Rated Electrical	Indoor/outdoor use					
Phase Monitors	Electrical protection for compressors					

AVAILABLE OPTIONS							
OPTIONS	AVAILABLE						
Extended Warranty	4 year extended compressor warranty						
Compressors	Equivalent compressors available from Bitzer and Carlyle						
Electrical	Compressor fusing, disconnects, circuit breakers and more						
Stainless Steel Pumps	1/3 HP to 25 HP on board pumps in multiple configurations & options						
Fluid Piping Upgrades	Flow meters, pressure gauges, low flow bypass valves, and more						
Coastal Protection/Hazardous Environments	Heresite coating, "Gold" and Copper condenser coils						
Low Ambient Protection	EC fan for temperature down to +10°F, Head pressure control for temperatures down to - 20°F, Heated receivers for temperature down to -40°F						
Other	Casters, service outlets, city water add-ons, heaters, etc.						
More options and customization available, contact factory for information: (888) 289 - 7299							

AVAILABLE MODEL NUMBER VOLTAGE REFERENCE

T3 (208-230/3/60) --- T4 (460/3/60) --- T5 (575/3/60)

PRODUCT INFORMATION										
MODELS AVAILABLE	COMPRESSOR		FAN MOTOR		RLA EA	LRA EA	МСА	мор	RECIRC. TANK	
R407C R404A	MODEL	QTY	HP	QTY	FLA EA	EA	EA			IANK
PAC150S3-T3-S			15	2	2.3	59.6	275	80	125	
PAC150S3-T4-S	3DTHR17ME	1			1.1	29	138	40	60	N/A
PAC150S3-T5-S					0.9	23.6	110	35	50	
PAC150S6-T3-S			15 2		2.3	59.6	275	80	125	
PAC150S6-T4-S	3DTHR17ME	1		2	1.1	29	138	40	60	N/A
PAC150S6-T5-S				0.9	23.6	110	35	50		

DRAKE REFRIGERATION INC

2900 SAMUEL DRIVE BENSALEM, PA 19020 (888) 289-7299 www.drakechillers.com